

# Trunkquility 2-way loudspeaker Model 2.1

Equipped with the same drivers as Trunkquility 2.0 this passive loudspeaker model reaches a third lower down in the bass due to its larger size. It allows only lower volumes due to its small sized drivers but offers the same very alive and bright sound reproduction over the whole frequency range as Trunkquility 2.0. For small to mid-size rooms. Lower volume does not refer to background-music level: with a maximum soundpressure level far over 90 dB @ 1m you can enjoy a grand orchestra, but you are not sitting in the first row.

## Passive 2-way loudspeaker

Crossover frequency:	2,500 Hz
Efficiency:	87 dB / 2,83 V @ 1 m
Power handling:	50 W contin. (IEC 268-5)
Amplifier load:	4 Ω Impedance
Dimensions (H x D):	ca. 71 x 23 cm (deviation possible; loudspeaker pairs always have the same height)
Weight:	ca. 14 kg
Drivers:	118 mm bass/mid-driver with glass fibre cone ( $\pm 3$ mm linear displacement and 32 mm voice coil) in vented cabinet, 22 mm high-frequency dome driver
Cabinet:	Made of massive wood trunks. Different domestic wood types possible: e.g. birch, oak, beech, pine, Douglas fir
Production time:	ca. 65 hours
Price:	€ 4,850,-- per pair incl. VAT (in birch)



TRUNKQUILITY

färber

HANDCRAFTED HIGH-END AUDIO SYSTEMS